

GENIE® PRODUCT SOLUTIONS



Genie®
A TEREX BRAND

TAKING YOU **HIGHER**™

Customers First Always

Partnering for Success

Our dedication to lifting you higher extends well beyond the physical reach of our products. We thrive on building satisfying customer relationships founded on the idea of partnership. Because you, our customer, are at the center of everything we do.

Since 1966, we've been developing products to solve your worksite challenges — and that process never ends. Our team of product managers and engineers uses your input to design new products, featuring the latest technology to meet your changing needs. Then we manufacture those products to stringent standards that help increase quality, lower costs and give you exceptional value for years to come.

Providing Superior Value

Our commitment doesn't end with the sale. Our dedicated service teams provide support when you need it most. Our extensive parts network ships most parts within 24 hours. Simply put, we're always working to help maximize your "up time" so you can be more successful.

Genie is driven by one goal: doing the right thing, at the right time for our customers. That's not just what we do; it's who we are. So tell us what you need. We're listening.

Material Lifts

Lift, lower or move heavy loads in a variety of applications.

- Sturdy construction, reliable performance and ease of use make these lifts favorites on a wide variety of job sites.
- These versatile lifts offer a large selection of models and options/ attachments providing the opportunity to create just the lift you need.



Compact Options for Every Load

For handling all your lifting needs faster and easier, these heavy-duty material lifts can be operated by one person who can easily lift, lower and move loads.



Super Hoist™ | 3.8, 5.6

Lift Height	3.80 - 5.60 m	12 ft 5.6 in - 18 ft 4.5 in
Lift Capacity	113 - 136 kg	250 lbs - 300 lbs
Weight*	34 - 37 kg	75 lbs - 82 lbs

Genie® Super Hoist (GH™) portable telescoping pneumatic hoist uses compressed air to lift up to 136 kg (300 lbs) to heights of 3.8 m (12 ft 5.6 in) or up to 113 kg (250 lbs) up to 5.60 m (18 ft 4.5 in).



Load Lifter™

Lift Height	1.70 m	5 ft 7 in
Lift Capacity	91 kg	200 lbs
Weight*	26 kg	58 lbs

The Genie Load Lifter (LL™) lifts up to 91 kg (200 lbs) to a height of 1.70 m (5 ft 7 in). Stores easily with compact dimensions of 1.10 m x 38 cm x 52 cm (45 x 15 x 20.5 in).



Genie® Lift™ | 4, 8, 10, 12

Lift Height	1.80 - 4.20 m	5 ft 11 in - 13 ft 9.5 in
Lift Capacity**	159 - 227 kg	350 lbs - 500 lbs
Weight*	51 - 196 kg	113 lbs - 433 lbs

The Genie Lift (GL™) lifts up to 227 kg (500 lbs) to heights of up to 4.20 m (13 ft 9.5 in). Customize the GL for your job with three bases, various load handling attachments and optional tyres and ladders.

* Weight may vary depending on options and/or country standards.

** With 30 cm (12 in) load center.

Ready to Work

Heavy-duty design, yet lightweight and portable. Genie® material lifts are quick to set up, require no tools and are ready to work in minutes.



Superlift Contractor™ | 12, 18, 24

Lift Height	3.40 - 7.32 m	11 ft 2 in - 24 ft
Lift Capacity**	295 kg	650 lbs
Weight*	102 kg - 157 kg	225 lbs - 347 lbs

** With 36cm (14in) load Center.

The Genie Superlift Contractor (SLC™) lifts 295 kg (650 lbs) to heights of up to 7.32 m (24 ft). Designed for the construction industry, the SLC offers extreme durability and easy transport.




Superlift Advantage™ | 5, 10, 15, 20, 25

Lift Height	1.49 - 7.94 m	4 ft 10.5 in - 26 ft .5 in
Lift Capacity**	295 - 454 kg	650 lbs - 1000 lbs
Weight*	98 - 204 kg	215 lbs - 450 lbs

** With 46 cm (18 in) load center.

The Genie Superlift Advantage (SLA™) is a manually operated material lift with multiple bases and load handling options. It lifts up to 454 kg (1,000 lbs) of material to heights of up to 3.49 m (11 ft 5.5 in) and up to 295 kg (650 lbs) to heights of 7.94 m (26 ft .5 in).



Super Tower™ | 20, 25

Lift Height	5.94 - 7.94 m	19 ft 6 in - 26 ft .5 in
Lift Capacity**	295 - 363 kg	650 lbs - 800 lbs
Weight*	230 - 252 kg	507 lbs - 555 lbs

** With 46 cm (18 in) load center.

The Genie Super Tower (ST™) telescopes theatrical lighting and scenery weighing up to 363 kg (800 lbs) and can lift to heights of up to 7.94 m (26 ft .5 in) Standard flat black anodized finish lets the ST blend in backstage.



Extreme Durability

Designed specifically for the construction industry, the SLC unit is durable, lightweight and portable.

The Ultimate Stage Hand

Lifts and supports lighting systems, sound systems and stage scenery.

Aerial Work Platforms

Economical solution for all of your access needs.

- All models offer quick setup and excellent manoeuvrability.
- Perfect for schools, churches, warehouses and more.
- Choose your option to configure the exact lift that you need (narrow, standard or wide base options, outreach on IWP™ unit).



AWP™-20S

Working Height	8.12 m	26 ft 1 in
Platform Height	6.12 m	20 ft 1 in
Lift Capacity	159 kg	350 lbs
Power	AC or DC	
Weight*	299 - 347 kg	660 - 766 lbs



IWP-20S

Working Height	8.15 m	26 ft 2 in
Platform Height	6.15 m	20 ft 2 in
Lift Capacity	159 kg	350 lbs
Power	AC or DC	
Weight*	565 - 658 kg	1,245 - 1,345 lbs



AWP-25S

Working Height	9.57 m	30 ft 10 in
Platform Height	7.57 m	24 ft 10 in
Lift Capacity	159 kg	350 lbs
Power	AC or DC	
Weight*	315 - 371 kg	694 - 817 lbs



IWP-25S

Working Height	9.44 m	30 ft 5 in
Platform Height	7.44 m	24 ft 5 in
Lift Capacity	159 kg	350 lbs
Power	AC or DC	
Weight*	585 - 630 kg	1,290 - 1,390 lbs



AWP-30S

Working Height	11.00 m	35 ft 6 in
Platform Height	9.00 m	29 ft 6 in
Lift Capacity	159 kg	350 lbs
Power	AC or DC or air motor power	
Weight*	331 - 393 kg	729 - 867 lbs



IWP-30S

Working Height	11.00 m	35 ft 6 in
Platform Height	9.00 m	29 ft 6 in
Lift Capacity	159 kg	350 lbs
Power	AC or DC	
Weight*	649 - 694 kg	1,430 - 1,530 lbs



AWP-36S

Working Height	13.10 m	42 ft 5 in
Platform Height	11.10 m	36 ft 5 in
Lift Capacity	159 kg	350 lbs
Power	AC or DC	
Weight*	461 - 502 kg	1,017 - 1,107 lbs



AWP-40S

Working Height	14.29 m	46 ft 4 in
Platform Height	12.29 m	44 ft 4 in
Lift Capacity	136 kg	300 lbs
Power	AC or DC	
Weight*	472 - 513 kg	1,040 - 1,130 lbs



Easy Transport

The unique rear mast pivot bar and lightweight design allow it to be easily loaded into a pickup truck.

* Weight will vary depending on options and/or country standards.

** 2 people indoor only

Genie® Runabout™ with Jib

To meet the demands of tight workspaces

- A jib version to our popular Genie® Runabout™ range to give our customers more choices in industrial and maintenance applications.
- Both models allow two-person occupancy indoors to get more done in a small amount of space.
- The 0.90 m x 0.75 m (2 ft 11 in x 2 ft 5.5 in) compact steel work platform enables the unit to be driven through industrial doorways with the operator on board.



GR™-12



Working Height	5.45 m	17 ft 4 in
Platform Height	3.45 m	11 ft 4 in
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	717 kg	1,581 lbs

GR-20J



Working Height	7.70 m	25 ft 3 in
Platform Height	5.70 m	18 ft 8 in
Lift Capacity	200 kg	440 lbs
Power	DC	
Weight*	2,250 kg	4,960 lbs

GR-15



Working Height	6.52 m	20 ft 10 in
Platform Height	4.52 m	14 ft 10 in
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	994 kg	2,192 lbs

GR-26J



Working Height	9.85 m	32 ft 4 in
Platform Height	7.85 m	25 ft 9 in
Lift Capacity	200 kg	440 lbs
Power	DC	
Weight*	2,650 kg	5,842 lbs

GR-20



Working Height	8.02 m	25 ft 9 in
Platform Height	6.02 m	19 ft 9 in
Lift Capacity	159 kg	350 lbs
Power	DC	
Weight*	1,112 kg	2,451 lbs

GRC™-12



Working Height	5.66 m	18 ft
Platform Height	3.66 m	12 ft
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	948 kg	2,090 lbs



QS™-12



Working Height	5.45 m	17 ft 4 in
Platform Height	3.45 m	11 ft 4 in
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	717 kg	1,581 lbs (Warehouse)
	730 kg	1,609 lbs (Retail)

QS-15



Working Height	6.52 m	20 ft 10 in
Platform Height	4.52 m	14 ft 10 in
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	994 kg	2,192 lbs (Warehouse)
	1,007 kg	2,220 lbs (Retail)

QS-20



Working Height	8.02 m	25 ft 9 in
Platform Height	6.02 m	19 ft 9 in
Lift Capacity	159 kg	350 lbs
Power	DC	
Weight*	1,112 kg	2,451 lbs (Warehouse)
	1,124 kg	2,479 lbs (Retail)

Streamlining Inventory Management

The Genie® QuickStock™ (QS) lift is designed to make your inventory picking faster, easier and safer than rolling stairs or manually propelled lifts.

Self-Propelled Scissor Lifts

Perfect solution for increasing worksite productivity.

- Electric models are great for indoor and outdoor applications with firm, level surfaces.
- Perfect for jobs that require greater lift capacity and maximum platform workspace.
- Rough Terrain models provide maximum productivity in more demanding outdoor worksites.



GS™-1530 & GS-1532

Working Height	6.57 m	21 ft
Platform Height	4.57 m	15 ft
Lift Capacity	272 kg	600 lbs
Power	DC	
Weight*	(30in) 1,233 kg	2,718 lbs
	(32in) 1,269 kg	2,797 lbs



GS-2646

Working Height	9.80 m	32 ft 1 in
Platform Height	7.80 m	25 ft 6 in
Lift Capacity	454 kg	1,000 lbs
Power	DC	
Weight*	2,447 kg	5,395 lbs



GS-1930 & GS-1932

Working Height	7.79 m	25 ft
Platform Height	5.79 m	19 ft
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	(30in) 1,498 kg	3,302 lbs
	(32in) 1,503 kg	3,313 lbs



GS-3246

Working Height	11.75 m	38 ft
Platform Height	9.75 m	32 ft
Lift Capacity	318 kg	700 lbs
Power	DC	
Weight*	2,812 kg	6,200 lbs



GS-2032

Working Height	7.90 m	25 ft 11 in
Platform Height	5.90 m	19 ft 5 in
Lift Capacity	363 kg	800 lbs
Power	DC	
Weight*	1,825 kg	4,024 lbs



GS-4047

Working Height	13.70 m	44 ft 11 in
Platform Height	11.70 m	38 ft 5 in
Lift Capacity	350 kg	770 lbs
Power	DC	
Weight*	3,221 kg	7,100 lbs



GS-2632

Working Height	9.93 m	32 ft
Platform Height	7.93 m	26 ft
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	1,956 kg	4,313 lbs



GS-2669 DC

Working Height	9.70 m	31 ft 9 in
Platform Height	7.70 m	25 ft 3 in
Lift Capacity	680 kg	1,500 lbs
Power	DC	
Weight*	(DC) 3,442 kg	7,588 lbs



GS-3232

Working Height	11.75 m	38 ft
Platform Height	9.75 m	32 ft
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	2,352 kg	5,185 lbs



GS-3369 DC

Working Height	11.75 m	38 ft 6 in
Platform Height	9.75 m	31 ft 11 in
Lift Capacity	454 kg	1,000 lbs
Power	DC	
Weight*	(DC) 3,623 kg	7,987 lbs



GS-2046

Working Height	8.10 m	26 ft
Platform Height	6.10 m	20 ft
Lift Capacity	544 kg	1,200 lbs
Power	DC	
Weight*	1,974 kg	4,351 lbs



GS-4069 DC

Working Height	14.12m	46 ft 3 in
Platform Height	12.12 m	39 ft 9 in
Lift Capacity	363 kg	800 lbs
Power	DC	
Weight*	4,810 kg	10,604 lbs

* Weight will vary depending on options and/ or country standards.

Self-Propelled Scissor Lifts



Hybrid Scissor Lift: “First on, Last off”

The Genie GS™-69 Bi-Energy series are the next evolution of the current Genie GS-69 DC and RT scissor lift series. Start on jobsites outside in moderate rough terrain and no available power; finish inside and switch to all-electric, no emissions or noise.



GS™-2669 BE

Working Height	9.70 m	31 ft 9 in
Platform Height	7.70 m	25 ft 3 in
Lift Capacity	680 kg	1,500 lbs
Power	DC	
Weight*	3,859 kg	8,504 lbs



GS-3369 BE

Working Height	11.75 m	38 ft 6 in
Platform Height	9.75 m	31 ft 11 in
Lift Capacity	454 kg	1,000 lbs
Power	DC	
Weight*	3,741 kg	8,243 lbs



GS-4069 BE

Working Height	14.12 m	46 ft 3 in
Platform Height	12.12 m	39 ft 9 in
Lift Capacity	363 kg	800 lbs
Power	DC	
Weight*	4,893 kg	10,815 lbs



Power and Performance

Powerful four-wheel drive RT scissor lifts have positive traction control that is ideal for increasing productivity in demanding outdoor worksites.



GS-2669 RT

Working Height	9.70 m	31 ft 9 in
Platform Height	7.70 m	25 ft 3 in
Lift Capacity	680 kg	1,500 lbs
Power	Diesel	
Weight*	3,376 kg	7,443 lbs



GS-3369 RT

Working Height	11.75 m	38 ft 6 in
Platform Height	9.75 m	31 ft 11 in
Lift Capacity	454 kg	1,000 lbs
Power	Diesel	
Weight*	3,557 kg	7,842 lbs



GS-4069 RT

Working Height	14.12 m	46 ft 3 in
Platform Height	12.12 m	39 ft 9 in
Lift Capacity	363 kg	800 lbs
Power	Diesel	
Weight*	4,744 kg	10,459 lbs



GS-3384 RT

Working Height	11.94 m	39 ft 2 in
Platform Height	9.94 m	32 ft 6 in
Lift Capacity	1,134 kg	2,500 lbs
Power	Diesel	
Weight*	5,445 kg	12,002 lbs



GS-3390 RT

Working Height	11.94 m	39 ft 2 in
Platform Height	9.94 m	32 ft 6 in
Lift Capacity	1,134 kg	2,500 lbs
Power	Diesel	
Weight*	5,557 kg	12,250 lbs



GS-4390 RT

Working Height	14.75 m	48 ft 4 in
Platform Height	12.75 m	41 ft 9 in
Lift Capacity	680 kg	1,500 lbs
Power	Diesel	
Weight*	5,973 kg	13,167 lbs

Expansive Platform

A large work deck with front extension and optional rear deck extension provides ample area for jobs requiring a large amount of platform space.



GS-5390 RT

Working Height	17.95 m	58 ft 10 in
Platform Height	15.95 m	52 ft 3 in
Lift Capacity	680 kg	1,500 lbs
Power	Diesel	
Weight*	7,639 kg	16,840 lbs



Self-Propelled Articulating Z-Booms Electric Powered, Bi-Energy and Hybrid

Your choice for reaching indoor working heights of 11.14 m (36 ft) to 20.16 m (65 ft 7 in).

- Ideal for “up and over” reach requirements in very confined areas and narrow passageways.
- Suitable for indoor and outdoor smooth surface use.
- Capable of passing through standard double doorways.
- Perfect for applications where quiet, emission free operation is required.



Z™-30/20N

Working Height	11.14 m	36 ft
Horizontal Reach	6.53 m	21 ft 5 in
Up & Over Clearance	3.86 m	12 ft 8 in
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	6,428 kg	14,170 lbs



Z-40/23N

Working Height	14.32 m	46 ft 5 in
Horizontal Reach	6.91 m	22 ft 8 in
Up & Over Clearance	6.48 m	21 ft 3 in
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	6,908 kg	15,230 lbs



Z-30/20N RJ

Working Height	10.89 m	35 ft 2 in
Horizontal Reach	6.25 m	20 ft 6 in
Up & Over Clearance	3.86 m	12 ft 8 in
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	6,450 kg	14,220 lbs



Z-40/23N RJ

Working Height	14.32 m	46 ft 5 in
Horizontal Reach	6.91 m	22 ft 8 in
Up & Over Clearance	6.48 m	21 ft 3 in
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	6,940 kg	15,300 lbs



Z-33/18

Working Height	12 m	39 ft 4 in
Horizontal Reach	5.57 m	18 ft 3 in
Up & Over Clearance	4.28 m	14 ft 1 in
Lift Capacity	200 kg	440 lbs
Power	DC	
Weight*	3,665 kg	8,080 lbs



Bi-Energy and Z-45/25 DC

Working Height	15.87 m	51 ft 6 in
Horizontal Reach	7.62 m	25 ft
Up & Over Clearance	7.24 m	23 ft 9 in
Lift Capacity	227 kg	500 lbs
Power	DC or Bi-Energy	
Weight*	(DC) 6,963 kg	15,350 lbs
	(Bi) 7,190 kg	15,850 lbs



Z-34/22N

Working Height	12.52 m	40 ft 6 in
Horizontal Reach	6.78 m	22 ft 3 in
Up & Over Clearance	4.65 m	15 ft 3 in
Lift Capacity	227 kg	500 lbs
Power	DC	
Weight*	5,171 kg	11,400 lbs



Bi-Energy and Z-45/25J DC

Working Height	15.94 m	51 ft 9 in
Horizontal Reach	7.65 m	25 ft 1 in
Up & Over Clearance	7.24 m	23 ft 9 in
Lift Capacity	227 kg	500 lbs
Power	DC or Bi-Energy	
Weight*	(DC) 7,394 kg	16,300 lbs
	(Bi) 7,620 kg	16,800 lbs



Bi-Energy and Z-34/22 DC

Working Height	12.52 m	40 ft 6 in
Horizontal Reach	6.78 m	22 ft 3 in
Up & Over Clearance	4.57 m	15 ft
Lift Capacity	227 kg	500 lbs
Power	DC or Bi-Energy	
Weight*	(DC) 5,179 kg	11,189 lbs
	(Bi) 5,632 kg	12,189 lbs



Z-60/37 DC and FE

Working Height	20.16 m	65 ft 7 in
Horizontal Reach	11.15 m	36 ft 7 in
Up & Over Clearance	7.39 m	24 ft 3 in
Lift Capacity	227 kg	500 lbs
Power	DC or FE	
Weight*	(DC) 7,530 kg	16,600 lbs
	(FE) 7,756 kg	17,100 lbs


* Weight may vary depending on options and/or country standards.



Self-Propelled Articulating Z-Booms Engine Powered

The perfect tool for reaching heights between 12.52 m (40 ft 6 in) and 43.15 m (141 ft) or reaching out a maximum of 21.26 m (69 ft 9 in).

- Z-boom design provides lifting versatility with “up and over” positioning and excellent outreach.
- Ideal for outdoor construction and industrial applications.
- Rough Terrain (RT) models are excellent for traveling over irregular or bumpy ground to a worksite.
- Models with oscillating axles provide a smoother ride over rough surface conditions.



Z™-34/22 IC		2WD		4WD	
Working Height	12.52 m	40 ft 6 in	12.54 m	40 ft 7 in	
Horizontal Reach	6.78 m	22 ft 3 in	6.78 m	22 ft 3 in	
Up & Over Clearance	4.57 m	15 ft	4.6 m	15 ft 1 in	
Lift Capacity	227 kg	500 lbs	227 kg	500 lbs	
Power	Diesel		Diesel		
Weight*	4,892 kg	10,786 lbs	4,929 kg	10,986 lbs	



Z-45/25 RT			
Working Height	15.97 m	51 ft 10 in	
Horizontal Reach	7.49 m	24 ft 7 in	
Up & Over Clearance	7.14 m	23 ft 5 in	
Lift Capacity	227 kg	500 lbs	
Power	Diesel		
Weight*	(4WD) 6,415 kg	14,144 lbs	



Z-45/25J RT			
Working Height	15.86 m	51 ft 6 in	
Horizontal Reach	7.52 m	24 ft 8 in	
Up & Over Clearance	7.14 m	23 ft 5 in	
Lift Capacity	227 kg	500 lbs	
Power	Diesel		
Weight*	(4WD) 6,460 kg	14,244 lbs	



Z-45XC			
Working Height	15.86 m	51 ft 6 in	
Horizontal Reach	7.55 m	24 ft 9 in	
Up & Over Clearance	7.22 m	23 ft 8 in	
Lift Capacity			
Unrestricted weight	300 kg	660 lbs	
Restricted weight	454 kg	1,000 lbs	
Power	Diesel		
Weight*	6,870 kg	15,145 lbs	



Z-51/30J RT			
Working Height	17.59 m	57 ft 8 in	
Horizontal Reach	9.37 m	30 ft 9 in	
Up & Over Clearance	7.39 m	24 ft 3 in	
Lift Capacity	227 kg	500 lbs	
Power	Diesel		
Weight*	7,394 kg	16,300 lbs	




Z-62/40			
Working Height	20.87 m	67 ft 11 in	
Horizontal Reach	12.42 m	40 ft 5 in	
Up & Over Clearance	7.8 m	25 ft 7 in	
Lift Capacity	227 kg	500 lbs	
Power	Diesel		
Weight*	10,281 kg	22,665 lbs	



Z-80/60			
Working Height	25.77 m	84 ft	
Horizontal Reach	18.29 m	60 ft	
Up & Over Clearance	8.83 m	29 ft	
Lift Capacity	227 kg	500 lbs	
Power	Diesel		
Weight*	(2WS) 16,284 kg	35,900 lbs	
	(4WS) 17,010 kg	37,500 lbs	



ZX-135/70			
Working Height	43.15 m	141 ft	
Horizontal Reach	21.26 m	69 ft 9 in	
Up & Over Clearance	9.91 m	32 ft 6 in (Riser Retracted)	
	23.01 m	75 ft 6 in (Riser Extended)	
Lift Capacity	272 kg	600 lbs	
Power	Diesel		
Weight*	20,092 kg	46,500 lbs	

Up, Out and Over

Articulating Z-booms provide the ultimate in lifting and working versatility with up, out and over positioning. You can get into spots that were never possible before with a Z-boom.

Self-Propelled Telescopic S-Booms

The lift you want when you need to reach out horizontally between 9.65 m (31 ft 8 in) and 27.43 m (90 ft) and reach heights of 14.20 m (46 ft) to 56.86 m (186 ft).

- Excellent choice when an operator needs to reach work at a distance where terrain and obstacles prevent close access.
- Models with jibs can access hard to reach locations above and below the obtained reach and manoeuvre platforms directly into place.
- Great for high performance applications where drive speed, lift speed and rough terrain capability are important.
- Track booms are ideal for working year-round by enhancing traction for travel in muddy, soft-soil, sandy, snowy and wet ground conditions and, they can also easily travel over harder surfaces like gravel, rock, concrete and asphalt, and sensitive turf.



S™-40 / S-40 TraX



Working Height	14.20 m	46 ft
Platform Height	12.20 m	40 ft
Horizontal Reach	9.65 m	31 ft 8 in
Lift Capacity	227 kg	500 lbs
Power	Diesel	
Weight*	(S-40) 5,420 kg	11,950 lbs
	(TraX) 6,564 kg	14,440 lbs

S-45 / S-45 TraX



Working Height	15.72 m	51 ft
Platform Height	13.72 m	45 ft
Horizontal Reach	11.18 m	36 ft 8 in
Lift Capacity	227 kg	500 lbs
Power	Diesel	
Weight*	(S-40) 6,709 kg	14,790 lbs
	(TraX) 7,927 kg	17,476 lbs

S-60 / S-60 TraX



Working Height	20.30 m	66 ft
Platform Height	18.30 m	60 ft
Horizontal Reach	15.48 m	50 ft 10 in
Lift Capacity	227 kg	500 lbs
Power	Diesel	
Weight*	(2WD) 9,308 kg	20,520 lbs
	(4WD) 9,385 kg	20,690 lbs
	(TraX 4WD) 11,353 kg	25,430 lbs

S-65 / S-65 TraX



Working Height	21.80 m	71 ft
Platform Height	19.80 m	65 ft
Horizontal Reach	17.10 m	56 ft 2 in
Lift Capacity	227 kg	500 lbs
Power	Diesel	
Weight*	(2WD) 10,024 kg	22,100 lbs
	(4WD) 10,102 kg	22,270 lbs
	(TraX 4WD) 12,299 kg	26,960 lbs

S-80 XC™



Working Height	26.38 m	86 ft
Platform Height	24.38 m	80 ft
Horizontal Reach	20.83 m	68 ft 4 in
Lift Capacity		
Unrestricted weight	300 kg	660 lbs
Restricted weight	454 kg	1,000 lbs
Power	Diesel	
Weight*	16,057 kg	35,400 lbs

S-85 XC



Working Height	27.74 m	91 ft
Platform Height	25.91 m	85 ft
Horizontal Reach	22.71 m	74 ft 6 in
Lift Capacity		
Unrestricted weight	300 kg	660 lbs
Restricted weight	454 kg	1,000 lbs
Power	Diesel	
Weight*	17,191 kg	37,900 lbs

* Weight will vary depending on options and/or country standards.



Super Booms, Heavy Duty model & Xtra Capacity™ Boom Lifts.

- Genie® Super Booms lifts combine maximum reach with exceptional manoeuvrability. They feature rugged diesel engine options, four-wheel drive and steer capabilities, and foam-filled rough terrain tyres for quick and easy positioning.
- Heavy Duty machines are designed for harsh environments including shipyards.
- With a platform load capacity up to 300 kg (660 lb) throughout the entire range of motion the Xtra Capacity boom lifts allow you to realize greater returns on your investment.



SX-105 XC™

Working Height	34.00 m	111 ft
Platform Height	32.00 m	105 ft
Horizontal Reach	24.38 m	80 ft
Lift Capacity		
Unrestricted weight	300 kg	660 lbs
Restricted weight	454 kg	1,000 lbs
Power	Diesel	
Weight*	19,300 kg	42,549 lbs



SX-125 XC

Working Height	40.15 m	131 ft 2 in
Platform Height	38.15 m	125 ft 2 in
Horizontal Reach	24.38 m	80 ft
Lift Capacity		
Unrestricted weight	300 kg	660 lbs
Restricted weight	454 kg	1,000 lbs
Power	Diesel	
Weight*	20,700 kg	45,636 lbs



SX-135 XC

Working Height	43.15 m	141 ft
Platform Height	41.15 m	135 ft
Horizontal Reach	27.43 m	90 ft
Lift Capacity		
Unrestricted weight	300 kg	660 lbs
Restricted weight	454 kg	1,000 lbs
Power	Diesel	
Weight*	21,546 kg	47,500 lbs



SX-150

Working Height	48.33 m	158 ft
Platform Height	46.33 m	152 ft
Horizontal Reach	24.38 m	80 ft
Lift Capacity**	340 kg	750 lbs
Power	Diesel	
Weight*	22,657 kg	49,950 lbs



SX-180

Working Height	56.69 m	186 ft
Platform Height	54.86 m	180 ft
Horizontal Reach	24.38 m	80 ft
Lift Capacity	340 kg	750 lbs
Power	Diesel	
Weight*	24,948 kg	55,000 lbs



S-100HD

Working Height	32.48 m	106 ft
Platform Height	30.48 m	100 ft
Horizontal Reach	22.26 m	73 ft
Lift Capacity	340 kg	1,250 lbs
Power	Diesel	
Weight*	(2WD) 18,035 kg	39,760 lbs
	(4WD) 18,275 kg	40,295 lbs



S-120HD

Working Height	38.58 m	126 ft
Platform Height	36.58 m	120 ft
Horizontal Reach	22.26 m	73 ft
Lift Capacity	340 kg	1,250 lbs
Power	Diesel	
Weight*	(2WD) 20,548 kg	45,300 lbs
	(4WD) 20,788 kg	45,830 lbs



Trailer-Mounted Z-Booms

Extremely versatile and easy to use.

- An excellent value in high reach equipment. The hydraulic outriggers and automatic machine levelling provide quick, efficient setup.
- A favourite with contractors and rental yards. The TZ™-50 has an industry-leading working range and an optional hybrid DC/gas charging system.



TZ-34/20

Working Height	12.36 m	40 ft
Platform Height	10.36 m	34 ft
Horizontal Reach	5.59 m	18 ft 4 in
Lift Capacity	181 - 200 kg	400 - 440 lbs
Power	DC	
Weight*	1,438 kg	3,170 lbs



TZ-50

Working Height	17.09 m	55 ft 6 in
Platform Height	15.09 m	49 ft 6 in
Horizontal Reach	8.89 m	29 ft 2 in
Lift Capacity	200 kg	440 lbs
Power	DC, Hybrid DC/Gas (gas for charging only)	
Weight*	2,025 kg	4,464 lbs



Easy to Manoeuvre and Position

The TZ-34/20 is lightweight and easy to manoeuvre, position and store. It meets the challenges of the working environment.

Increase Your Productivity

The exclusive self-levelling system on the TZ-50 allows the operator to set up the machine in less than 60 seconds when the operator deploys all four outriggers simultaneously.

* Weight will vary depending on options and/ or country standards.

** Unrestricted load capacity of 300 kg (660 lbs) and a restricted capacity of 454 kg (1,000 lbs).

Telehandlers

Multiply your return on investment

- Extreme versatility makes Genie® telehandlers a valuable and cost-effective investment for any worksite.
- Choose a compact rough terrain unit when you need a nimble yet powerful machine for high productivity in confined or limited access areas.



GTH™-2506

Max Lift Capacity	2,500 kg	5,511 lbs
Max Lifting Height	5.79 m	19 ft
Max Horizontal	3.35 m	10 ft 12 in
Weight*	4,580 kg	10,100 lbs



GTH-3007

Max Lift Capacity	3,000 kg	6,614 lbs
Max Lifting Height	6.89 m	22 ft 7 in
Max Horizontal	3.99 m	13 ft 1 in
Weight*	5,970 kg	13,161 lbs



GTH-4014

Max Lift Capacity	4,000 kg	8,818 lbs
Max Lifting Height	13.57 m	44 ft 6 in
Max Horizontal	9.08 m	29 ft 9 in
Weight*	10,225 kg	22,542 lbs



GTH-4018

Max Lift Capacity	4,000 kg	8,818 lbs
Max Lifting Height	17.61 m	57 ft 9 in
Max Horizontal	13.36 m	43 ft 10 in
Weight*	11,980 kg	26,411 lbs



Expand your options

- Select from a wide variety of attachments that will expand work capabilities to match the exact job you need to tackle.
- Ideal for masonry, construction, farming or landscape applications.

* Weight will vary depending on options and/or country standards.



Light Towers

(not CE products)



- 8.76 m - 9.14 m (28 ft 9 in - 30 ft) floodlight towers provide 4,000 watts of light.
- Industry leading technology and quality engineering make Terex® light towers the best solution to illuminate your jobsite.
- New LED light towers provide 40% reduction in fuel costs with five times longer bulb life. Battery powered units offer no noise or emissions and do not require fuel during operation.



RL™4

Tower Height	9.14 m	30 ft
Width (Stowed)	1.37 m	4 ft 6 in
Length (Stowed)	4.33 m	14 ft 2 in
Weight	783 kg	1,725 lbs



AL™4

Tower Height	9.14 m	30 ft
Width (Stowed)	1.56 m	5 ft 2 in
Length (Stowed)	4.55 m	14 ft 11 in
Dry Weight	885 kg	1,950 lbs



AL4L

Battery powered option


Tower Height	9.14 m	30 ft
Width (Stowed)	1.55 m	61 in
Length (Stowed)	4.55 m	14 ft 11 in
Dry Weight	885 kg	1,950 lbs



AL4L

6kW generator option

Tower Height	9.14 m	30 ft
Width (Stowed)	1.55 m	61 in
Length (Stowed)	4.65 m	15 ft 3 in
Dry Weight	949 kg	2,092 lbs



AL5

Tower Height	9.14 m	30 ft
Width (Stowed)	2.04 m	6 ft 9 in
Length (Stowed)	4.65 m	15 ft 3 in
Dry Weight	1,016 kg	2,239 lbs



AL5 HT

Tower Height	8.76 m	28 ft 9 in
Width (Stowed)	2.07 m	6 ft 9 in
Length (Stowed)	2.49 m	8 ft 2 in
Dry Weight	1,182 kg	2,605 lbs



AL5L

Tower Height	9.14 m	30 ft
Width (Stowed)	2.03 m	80 in
Length (Stowed)	4.65 m	15 in 3 in
Dry Weight	1,283 kg	2,828 lbs



Models

Portable Material Lifts

Super Hoist™	Load Lifter™
Genie® Lift™	Superlift Contractor™
Superlift Advantage™	Super Tower™

Aerial Work Platforms

AWP™ Super Series

AWP-20S	AWP-25S
AWP-30S	AWP-36S
AWP-40S	

IWP™ Super Series

IWP-20S
IWP-25S
IWP-30S

Runabouts™

GR™-12	GR-15
GR-20	GRC™-12
GR-20 J	GR-26 J

QuickStock™

QS™-12
QS-15
QS-20

Self-Propelled Scissor Lifts

GS™-1530	GS-1532
GS-1930	GS-1932
GS-2032	GS-2632
GS-3232	GS-2046
GS-2646	GS-3246
GS-4047	GS-2669 DC
GS-3369 DC	GS-4069 DC
GS-2669 BE	GS-3369 BE
GS-4069 BE	GS-2669 RT
GS-3369 RT	GS-4069 RT
GS-3384 RT	GS-3390 RT
GS-4390 RT	GS-5390 RT

Booms

Self-Propelled Articulating Z™-Booms

Z™-30/20N	Z-30/20N RJ
Z-33/18	Z-34/22DC
Z-34/22 Bi-Energy	Z-34/22N
Z-34/22 IC	Z-40/23N
Z-40/23N RJ	Z-45/25 DC
Z-45/25J DC	Z-45/25 Bi-Energy
Z-45/25J Bi-Energy	Z-45/25 RT
Z-45/25J RT	Z-45XC
Z-51/30J RT	Z-60/37 DC
Z-60/37FE	Z-62/40
Z-80/60	ZX-135/70

Self-Propelled Telescopic S™-Booms

S™-40	S-45
S-40 TraX	S-45 TraX
S-60	S-65
S-60 TraX	S-65 TraX
S-80 XC™	S-85 XC
SX-105 XC	SX-125 XC
SX-135 XC	SX-150
SX-180	S-100 HD
S-120 HD	

Trailer-Mounted Z™-Booms

TZ™-34/20
TZ-50

Telehandlers

GTH™-2506	GTH-3007
GTH-4014	GTH-4018

Trailer-Mounted Light Towers

(not CE certified)

RL™4	AL™4
AL5	AL5 HT
AL4L	AL5L



Europe, Middle East, Africa and Russia

To view all our locations visit www.genielift.co.uk/locations

Telephone +44 800 988 3739 (Toll Free for UK/Ireland)

Fax +44 (0)1476 584334 · Email: AWP-InfoEurope@terex.com

www.genielift.co.uk

Worldwide Manufacturing And Distribution

Australia · Brazil · Caribbean · Central America · China · France · Germany · Italy · Japan · Korea · Mexico
Russia · Southeast Asia · Spain · Sweden · United Arab Emirates · United Kingdom · United States

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2017 Terex Corporation. Small Family 138K 0309L. Part No.B109385UK.

